

TECHNICAL DATA

Vehicle Type: 911

Engine Type: officially - 2000
internally - 901/01

Engine

Type.....	air cooled four stroke cycle Otto engine, unitized with clutch, transmission, and differential to form one assembly at rear of vehicle	
Number of cylinders	6	
Cylinder arrangement	horizontally opposed six, three cylinders in each bank	
Bore	80 mm (3.15 in.)	
Stroke.....	66 mm (2.60 in.)	
Total piston displacement	1991 cc (121.5 cu. in.)	
Compression ratio.....	9 : 1	
Total weight (dry)	approx. 84 kp (185 lbs)	
Crankcase	two-piece, light alloy	
Cylinders.....	individual	
Cylinder material	light alloy	
Cylinder bore.....	cast iron coat	
Cylinder heads	individual for each cylinder, light alloy	
Valve seat inserts	shrunk in	
Valve guides.....	shrunk in, special bronze	
Spark plug seat inserts.....	helicoil	
Crankshaft	forged	
Crankshaft bearings	8 plain journal bearings	
Main bearing 1 thru 7	split inserts, tri-metal	
Main bearing 8.....	one-piece sleeve, hard lead	
Main bearing 1.....	guide bearing	
Connecting rods	forged steel, H-section shank	
Big end bearings.....	tri-metal	
Piston pin bushings.....	pressed in, bronze	
Pistons	light alloy	
Piston rings	2 compression rings, 1 oil scraper	
Valve timing	OHC, 1 cam per cylinder bank	
Camshafts	cast; 3 plain bearings directly in camshaft housing	
Camshaft drive.....	by chains	
Valve arrangement	overhead	
Valve springs.....	2 coil springs per valve	
Valve clearance (adjust cold):		
intake.....	0.10 mm (.004 in.)	measure between valve and rocker arm
exhaust.....	0.10 mm (.004 in.)	
Valve timing with 1 mm(.040 in.)		
valve clearance:		
intake opens before TDC....	29°	
intake closes after BDC	39°	
exhaust opens before BDC ...	39°	
exhaust closes after TDC....	19°	
Cooling	air cooled by blower on generator shaft	
Cooling blower drive.....	off crankshaft by V-belt	
Blower air flow.....	1390 l/sec at 6100 rpm (49 cfs at 6100 rpm)	
Lubrication	forced feed, dry sump	

Oil cooling.....	oil cooler on crankcase in blower air stream
Oil pressure indication.....	electrically controlled
Ignition type.....	battery
Ignition coil type.....	TK 12A 10 mV
Distributor type.....	Bosch JFR 6
Contact breaker gap.....	0.4 mm (.016 in.)
Ignition firing point.....	TPC
Firing order.....	1-6-2-4-3-5
Spark plug threads.....	Bosch W 250 P 21
Electrode gap.....	0.35 mm (.014 in.)

Clutch

Type.....	single plate, dry, M 215 K - Fichtel and Sachs
Pedal free travel.....	approx. 20 mm (.8 in.)
Total facing area.....	203 cm ² (31.5 sq. in.)

Fuel System

Carburetors.....	6 overflow carburetors Solex, type 40 PI from engine No. 907 001 on
Air cleaner.....	2 triple throat carburetors Weber, type 40 IDA 3 C and 3 C 1
Fuel pumps.....	intake silencer with micronite filter cartridge
Deliver pressure.....	1 electric and 1 mechanical twin pump
electric pump.....	0.22 to 0.30 atm (3.23 to 4.41 psi)
mechanical pump.....	0.18 to 0.22 atm (2.65 to 3.23 psi)
Fuel screen.....	in fuel tank
Fuel filter.....	in fuel pumps

Electrical System

Operating voltage.....	12 Volt
Battery.....	12 V / 84 Ah
Generator.....	Bosch KI-14V 35A
Voltage regulator.....	Bosch VDN 1
Crankshaft/generator ratio.....	approx. 1:1.4
Starter motor.....	Bosch EB (L) 12V 0.8 (AL 50/20 W 12)
2 headlamps, high and low beam: with symmetric low beam .. with asymmetric low beam ..	45/40 Watts each (left-hand drive countries) 45/40 Watts each
2 clearance lights: in headlamps for all countries except USA; in directional blinkers for USA.....	4 Watts each

2 tail lights (in directional blinker and stop light units).....	5 Watts each
2 front directional blinkers	18 Watts each
2 combination blinkers and stop lights	18 Watts each
2 license plate lights	4 Watts each
1 backup light	25 Watts
Interior light:	
2 in Coupe models	10 Watts each
Tachometer illumination	2 Watts
High beam indicator	2 Watts
Directional signal pilot light	2 Watts
Combination instrument cluster illumination	2 Watts
Generator control lamp	2 Watts
Oil pressure indicator lamp	2 Watts
Speedometer illumination	2 Watts

Transmission and Rear Axle

Type	Integral 5-speed transmission and differential
Transmission	5 forward speeds with Porsche servo-synchromesh
Gear ratios - see Transmission Diagram, Group R	
Reverse gear ratio	i = 3,1473
Gearshift mechanism	mechanical rod, floor mounted shift lever
Axle drive	spiral bevel gears, bevel gear differential, limited slip differential optional
Reduction ratio	i = 4,428

Chassis

Frame	welded sheetmetal box-section frame unitized with body
Front wheel suspension	independently suspended on struts and transverse arms
Rear wheel suspension	independently suspended on longitudinal links, powered over half-axes
Front wheel springing	1 round longitudinal torsion bar per wheel
Rear wheel springing	1 round transverse torsion bar per wheel
Attitude of rear radius arms	Coupe = 30° (nominal inclination)
Front shockabsorbers	acting as suspension struts
Rear shockabsorbers	telescopic, double-action
Stabilizer	front, transverse
Steering	ZF rack and pinion with hydraulic damper
Steering ratio (total)	1 : 16,5 overall
Steering damper	hydraulic, double-acting
Steering wheel turns lock-to-lock	approx, 2,8
Smallest turning circle (diameter)	approx, 10,3 m (33,8 ft)
Toe-in, front	+ 15' to + 20' per wheel under load, steering box in center position
Toe-in, rear	0°

Camber, front	0° + 20°
Camber, rear	- 1° 15' + 20°
Steering axis inclination	10° 56' + 45°
Caster	6° 45' + 45°
Angle variation each side	40° until 1° 10' (curve inside wheel set to 20°)
Wheel rims	drop center rims 4 1/2 J x 15
Wheels	165 HR 15
Tires	perforated steel discs
Normal tire pressures:	
front	normal highway driving 1.8 arm (26.5 psi)
rear	normal highway driving 2.0 arm (29.4 psi)
	high speed expressways 2.0 arm (29.4 psi)
	high speed expressways 2.2 arm (32.3 psi)
Service brakes (foot brake)	discs
Service brake actuation	hydraulic
Total effective brake area	185 cm ² (28.7 sq. in.)
Front brake disc diameter	282 mm (11.1 in.)
Rear brake disc diameter	285 mm (11.2 in.)
Parking brake	mechanical, acting on rear wheels
Chassis lubrication	individual grease nipples
Body	
Type	All-steel body unitized with frame, declining front contour,
Doors	fastback rear in Coupes
Door width	2 doors hinged on front posts
Door swing angle	1050 mm (41.3 in.) average
Windows:	approx. 70°
windshield	one-piece, constant radius
door windows	crank lowered, with vent panel
rear side windows	hinged, with position lock
rear window	one-piece, curved
type of glass	safety glass
windshield wipers	electric, 2 parallel wiper arms
Compartment lids:	
front	hinged at rear, with hydraulic prop, opened from passenger compartment
rear	hinged at front, with hydraulic prop, opened from passenger compartment
Seats:	
Seating capacity	2/2
front seats	2 fully reclining bucket-type seats
rear seats	2 occasional seats, folding forward to form luggage platforms
Instrument panel	speedometer with odometer and trip mileage counter, clearance light control lamp
	illuminated electric tachometer with high beam indicator and directional indicator pilot lamps:
	combination instrument cluster including oil temperature gauge, oil pressure gauge, and generator control lamp - illuminated;
	clock;
	3-position windshield wiper switch on steering column;
	ignition/starter switch, light switch

Instrument panel (cont'd)	cigar lighter, ashtray, locking glove compartment, hand grip blinker-dimmer-flasher switch on steering column, steering wheel with signal horn button
Interior trim:	
floor	rubber mats
center tunnel	front with rubber padding, rear with carpets
forward side panels	carpet covered
doors and side panels	upholstered
headlining	leatherette
heating	hot air, remotely controlled, 2 defroster nozzles at windshield, 2 hot air outlets in side members below doors
Ventilation	fresh air outlets thru defroster nozzles and outlets in side members below doors
Miscellaneous:	
bumpers	front and rear with 2 overriders each
spare tire	concealed under locked front lid
fuel tank	under front lid
tools and accessories	under front lid

Weights and Measures

Wheelbase	2211 mm (87, 05 in.)	
Track, front	1337 mm (52, 64 in.)	from chassis No: 305 101 1353 mm (53, 23 in.)
Track, rear	1317 mm (51, 85 in.)	from chassis No: 305 101 1321 mm (52, 03 in.)
Length	4163 mm (163, 9 in.)	
Width	1610 mm (63, 39 in.)	
Height (empty), Coupe	1320 mm (51, 97 in.)	
Body overhang, front	865 mm (34, 1 in.)	
Body overhang, rear	1055 mm (41, 5 in.)	
Ground clearance, loaded	150 mm (5, 9 in.)	
Chassis clearance	140 mm (5, 5 in.)	
Empty weight (DIN) Coupe	1080 kp (2380 lbs)	
Maximum permissible weight (total)	1400 kp (3086 lbs)	
Maximum axle load, front	600 kp (1323 lbs)	
Maximum axle load, rear	840 kp (1852 lbs)	
Engine weight, complete (w/o oil)	approx. 184 kp (406 lbs)	
Transmission weight, complete (w/ oil)	approx. 50 kp (110 lbs)	

Capacities

Fuel tank	approx. 62 liters incl. 6 liters reserve (16,4 US gals incl. 1,6 gals reserve)
Engine and oil tank	approx. 9 liters premium HD oil, summer SAE 30, winter SAE 20 (9,5 US qts)
Transmission and differential	approx. 2,5 liters Hypoid SAE 90 (2,6 US qts)
Brake fluid reservoir	approx. 0,2 liters (7 fl. oz)
Windshield washer reservoir	approx. 2,0 liters (2,1 US qts)

Performance

Horsepower.....	130 DIN/HP (148 SAE/HP) at 6100 rpm
Maximum torque.....	17.8 mkp (128.7 lbs/ft) at 4200 rpm
Mean piston speed at max. power	13.4 m/sec (44 ft/sec)
Mean working pressure at	11.3 kp/cm ² (161 psi)
Maximum fuel consumption.....	225 g/Psh at 3400 rpm
Maximum speed.....	210 kmh (130 mph)
Specific power output.....	65 DIN-HP/liter (1.22 SAE-HP/cu. in.)
Power/weight ratio	8.8 DIN kp/HP (17 lbs/SAE HP)
Road speed in gears (theoretical)	see Transmission Diagram, Group R
Fuel Consumption	
Normal fuel consumption	9.6 liters/100 km (24.5 mpg US)
(DIN 70030)	
Required fuel octane rating.....	approx. 98 - 100 ROZ

SUPPLEMENTS

GROUP **TD**

TECHNICAL DATA

TECHNICAL DATA

Vehicle Type: 911 S

Engine Type: 2000 S

Engine

Type	air cooled four-stroke cycle Otto engine, unitized with clutch, transmission, and differential at rear of vehicle
Number of cylinders	6
Cylinder arrangement	horizontally opposed six, three cylinders in each bank
Bore	80 mm (3.15")
Stroke	66 mm (2.60")
Total piston displacement	1991 cc (121.5 cu.in)
Compression ratio	9.8:1
Total weight (dry)	approx. 184 kp (406 lbs)
Crankcase	two-piece, light alloy
Cylinders	removable individual units
Cylinder material	Biral (cast iron liner with light alloy cooling fin jacket)
Cylinder heads	light alloy, individual for each cylinder
Valve seat inserts	shrunk in
Valve guides	special bronze, shrunk in
Spark plug seat inserts	Helicoil
Crankshaft	forged
Crankshaft mounting	8 plain journal bearings
Main bearings 1 thru 7	tri-metal split inserts
Main bearing 8	hard lead sleeve
Main bearing 1	thrust bearing
Connecting rods	soft nitrated forged steel
Big end bearings	tri-metal
Piston pin bushings	Kuprodur, machined
Pistons	forged light alloy, box-shaped
Piston rings	2 compression rings, 1 oil scraper
Valve timing	OHC, 1 cam per cylinder bank
Camshafts	cast steel, in 3 plain bearings in base metal of camshaft housing
Camshaft drive	through chains
Valve arrangement	overhead
Valve springs	2 coil springs per valve
Valve clearance (adjust cold):	
intake	0.10 mm (.004")
exhaust	0.10 mm (.004")
	measured between valve and rocker arm
Valve timing with 1 mm (.040")	
valve clearance:	
intake opens before TDC	29°
intake closes after BDC	39°
exhaust opens before BDC	39°
exhaust closes after TDC	19°
Cooling	air cooled by blower on generator shaft
Cooling blower drive	off crankshaft by V-belt
Blower air flow	1390 l/sec 6100 rpm (49 cfs 6100 rpm)
Lubrication	forced feed, dry sump

Oil cooling	oil cooler on crankcase in air stream of blower
Oil pressure indication	electrical
Ignition type	battery
Ignition coil type	TK 12 A 10mV
Distributor type	Bosch 0231158002
Contact breaker gap	yellow nonmenclature plate
Ignition firing point	31° before TDC 6000 rpm
Firing order	1-6-2-4-3-5
Spark plug type	Bosch W 265 P 21
Spark plug threads	14 x 1.25 mm
Electrode gap	0.35 mm (.014")
C clutch	
Type	single plate, dry, M 215 K Fichtel & Sachs
Pedal free travel	approx. 20 mm (.8")
Total facing area	203 cm ² (31.5 sq. in.)
Fuel system	
Carburetors	Weber 40 IDA (S), or 40 IDS 3 C and 3 C 1, respectively
Air cleaner	induction silencer with microfine filter cartridge
Fuel pump	1 electrical fuel pump
Delivery pressure	0.22 to 0.30 atm (3.23 to 4.41 psi)
Delivery rate	900 cc/min (30.4 fl. oz.)
Fuel screen	in fuel tank
Fuel filter	in fuel pump
Electrical System	
Operating voltage	12 Volts
Battery rating	12 V, 45 Ah
Alternator	Bosch KI-14 V 35 A
Voltage regulator	Bosch VDN 1
Crankshaft/alternator rpm ratio	approx. 1:1.4
Starter motor	Bosch EB (L) 12 V 0.8 (AL 50/20 W 12)
2 headlamps, high and low beam:	
with asymmetric low beam	45/40 Watts each
with asymmetric low beam	45/40 Watts each
2 clearance lights:	
in headlamps for all countries except	
USA; in directional blinkers for USA	4 Watts each

2 tail lights in blinker/stop light units	5 Watts each
2 front directional blinkers	18 Watts each
2 combination blinker/stop lights	18 Watts each
2 license plate lights	4 Watts each
1 backup light	25 Watts
2 interior lights (Coupe)	10 Watts each
Tachometer illumination	2 Watts
High beam indicator	2 Watts
Blinker indicator	2 Watts
Multi-gauge cluster illumination	2 Watts
Alternator control lamp	2 Watts
Oil pressure control lamp	2 Watts
Speedometer illumination	2 Watts

Transmission and Rear Axle

Type	integral transmission and differential
Transmission	5 forward speeds with Porsche servo-synchromesh
Gear ratios	see transmission diagram, Group R
Reverse gear ratio	$i = 3.1473$
Gearshift mechanism	mechanical rod, floor mounted shift lever
Differential drive	spiral bevel gears, bevel gear differential, limited slip differential optional
Reduction ratio	$i = 4.428$

Chassis

Frame	welded sheetmetal box-section underbody unitized with body
Front wheel suspension	independently suspended on struts and transverse arms
Rear wheel suspension	independently suspended on longitudinal links with half-axle drive
Front wheel springing	1 round longitudinal torsion bar per wheel
Rear wheel springing	1 round transverse torsion bar per wheel
Attitude of rear radius arms	Coupe = 30° nominal inclination
Front shock absorbers	acting as suspension struts
Rear shock absorbers	telescopic, double-action
Stabilizer	front, transverse mounted
Steering type	ZF rack and pinion
Steering ratio	1:16.5 overall
Steering wheel turns lock-to-lock	approx. 2.8
Smallest turning circle diameter	approx. 10.3 m (33.8')
Toe-in, front	+ $40'$ (preloaded with 15 kp or 33.1lbs)
rear	0°

Camber, front	0 ± 20'
Steering axis inclination	10° 56'
Caster	7° 45'
Angle variation	40' to 10' (increasing toe-in)
Wheels	forged light alloy
Wheel rims	drop center rims 4 1/2 J x 15
Tires	165 HR 15
Nominal tire pressures:	
front	1.8 atm (26.5 psi)
rear	2.2 atm (32.3 psi)
fast driving (Autobahn)	2.0 atm (29.4 psi)
normal highway speeds	2.2 atm (32.3 psi)
fast driving (Autobahn)	2.2 atm (32.3 psi)
Service brake (foot brake)	discs
Service brake actuation	hydraulic
Total effective brake area	185 cm ² (28.7 sq. in.)
Brake disc diameter, front	282 mm (11.1"), vented disc
rear	285 mm (11.2"), vented disc
Parking brake	mechanical, acting on rear wheels
Chassis lubrication	individual grease nipples
Body	
Type	All-steel body unitized with frame, declining front contour,
Doors	2 doors hinged on front posts
door width	1050 mm (41.3") average
door swing angle	approx. 70°
Windshield	one-piece, constant radius
door windows	crank-downed, with vent panel
rear side windows	hinged, with position lock
rear window	one-piece, curved
type of glass	safety-glass
windshield wipers	electrical, 2 parallel wiper arms
Compartment lids:	
front	hinged at rear, with hydraulic prop, opened from passenger compartment
rear	hinged at front, with hydraulic prop, opened from passenger compartment
Seats:	
seating capacity	2/2
front seats	2 fully reclining bucket-type seats
rear seats	2 occasional seats, folding forward to form luggage platforms
Instrument panel	illuminated speedometer with odometer and trip mileage counter and clearance light control lamp;
	illuminated electric tachometer with high beam indicator and directional indicator pilot lamps;
	multi-gauge cluster with oil temperature gauge, oil pressure gauge, and alternator control lamp (illuminated); clock;
	3-position windshield wiper switch on steering column;
	ignition/starter switch, light switch

Instrument panel (cont'd)	cigar lighter, ashtray, locking glove compartment, hand grip, blinker-dimmer-flasher switch on steering column, steering wheel with signal horn button
Interior trim:	
floor	carpeted
center tunnel	rubber padded front, carpeted rear
forward side panels	carpeted
doors and side panels	upholstered
headlining	leatherette
heating	hot air, remotely controlled, 2 defroster nozzles at windshield, 2 hot air outlets in side members below doors
Ventilation	fresh air outlets thru defroster nozzles and outlets in side members below doors
Miscellaneous:	
bumpers	front and rear with 2 overrides each
spare tire	concealed under locked front lid
fuel tank	beneath luggage compartment
tool and accessories	in luggage compartment

Weights and Measures

Wheelbase	2211 mm (87.05")
Track, front	1353 mm (53.27")
rear	1325.4 mm (52.18")
Length	4163 mm (163.9")
Width	1610 mm (63.39")
Height (empty), Coupe	1320 mm (51.97")
Body overhang, front	865 mm (34.06")
rear	1055 mm (41.54")
Ground clearance, loaded	150 mm (5.91")
Chassis clearance	140 mm (5.51")
Empty weight (DIN), Coupe	1030 kp (2271 lbs)
Maximum permissible weight (total) ..	1400 kp (3086 lbs)
Maximum axle load, front	600 kp (1323 lbs)
rear	840 kp (1852 lbs)
Engine weight, complete (w/o oil)	184 kp (406 lbs)
Transmission weight, complete, with oil	approx. 50 kp (110 lbs)

Capacities

Fuel tank	approx. 62 liters incl. 6 liters reserve (16.4 US gals incl 1.6 gals reserve)
Engine and oil tank	approx. 9 liters premium HD oil (9.5 US qts) summer SAE 30, winter SAE 20
Transmission and differential	approx. 2.5 liters Hypoid SAE 90 (2.6 US qts)
Brake fluid reservoir	approx. 0.2 liters (7 fl.oz.)
Windshield washer reservoir	approx. 2.0 liters (2.1 US qts)

Performance

Horsepower rating, maximum	160 DIN HP (180 SAE HP) 6600 rpm
Maximum torque	18.2 mkgp (131.6 lbs/ft) 5200 rpm
Mean piston speed at max. power	14.5 m/sec (47.6 ft/sec)
Mean working pressure at max. power	11.0 kpc/cm ² (156 psi)
Minimum fuel consumption	225 g/psh 2000 rpm
Maximum speed	225 kmh (140 mph)
Specific power output	80 DIN HP/liter (1.48 SAE HP/cu.in)
Power/weight ratio (road ready)	6.85 hp/DIN HP (12.6 lbs/SAE HP)
Road speed in gears (theoretical)	see transmission diagram, Group R
Nominal fuel consumption	10.2 l/100 km (23.0 mpg US)
Required fuel octane rating	approx. 98-100 ROZ (Research Octane Rating)

Vehicle Type: 911 T

Engine Type: 2000 T

Engine

Type	air cooled four stroke cycle Otto engine, unitized with clutch, transmission, and differential, forming a power train at rear of vehicle
Number of cylinders	6
Cylinder arrangement	horizontally opposed six, three cylinders in each bank
Bore	80 mm (3.15")
Stroke	66 mm (2.60")
Total piston displacement	1991 cc (121.5 cu. in.)
Compression ratio	8.6:1
Total weight, dry	approx. 184 kg (406 lbs)
Crankcase	two piece, light alloy
Cylinders	individual
Cylinder material	grey cast iron
Cylinder heads	individual for each cylinder, light alloy
Valve seat inserts	shrunk in
Valve guides	shrunk in, special bronze
Spark plug seats	helicoil inserts
Crankshaft	forged
Crankshaft main bearings	8 plain journal bearings
Main bearings 1 - 7	split inserts, tri-metal
Main bearing 8	one piece sleeve, hard lead
Main bearing 1	thrust bearing
Connecting rods	forged steel
Big end bearings	tri-metal
Piston pin bushings	machined Kuprodur
Pistons	die cast (Autotherm.)
Piston rings	2 compression rings, 1 oil scraper
Valve timing	OHC, 1 cam per cylinder bank
Camshafts	cast steel, in 3 plain bearings directly in camshaft housing
Camshaft drive	by chains
Valve arrangement	overhead
Valve springs	2 coil springs per valve, or 1 coil spring per valve, respectively
Valve clearance (adjust cold):	
intake	0.10 mm (.004")
exhaust	0.10 mm (.004")
Valve timing with 1 mm (.040") valve clearance:	
intake opens	15° BTC
intake closes	29° ABC
exhaust opens	41° BBC
exhaust closes	5° BTC
Cooling	air cooled by blower on generator shaft
Cooling blower drive	off crankshaft by V-belt
Blower air flow	1320 ltr/sec (47 cfs) at 5800 rpm
Lubrication	forced feed, dry sump

Oil cooling	oil cooler on crankcase in blower air stream
Oil pressure indication	electrically controlled
Ignition type	battery
Ignition coil type	TK 12A 10 mV
Distributor type	Marelli S112AX
Contact breaker gap	0.4 mm $\pm$ 0.03 mm (.016" $\pm$.001"), or dwell angle of $40^\circ \pm 3^\circ$
Ignition firing point	350° BTC at 6000 rpm
Firing order	1-6-2-4-3-5
Spark plugs	Bosch W 230 T 30, Berni 240/14/3
Spark plug threads	14x1, 25 mm
Electrode gap	0.6 mm (.024")
Clutch	
Type	single plate, dry, M215K Fichiel + Sachs
Pedal free travel	approx. 20 mm (.8")
Total facing area	203 cm ² (31.5 sq. in.)
Fuel System	
Carburetors	Weber Type 40 IDT 3C and 40 IDT 3C1
Air cleaner	intake silencer with micron filter cartridge
Fuel pump	1 electric fuel pump
Fuel delivery pressure	0.28 - 0.33 atm (4.1 - 4.9 psi) for Bendix pump
Fuel delivery rate	0.28 - 0.30 atm (4.1 - 4.4 psi) for Hardi pump
Fuel filtering	900 cc (30.4 fl. oz.) per minute
	filtering screen in fuel tank and pump
Electrical System	
Operating voltage	12V
Battery	12V/45Ah
Alternator	Motorola 14V 490W
Voltage regulator	Motorola
Crankshaft/generator ratio	approx. 1:1.4
Starter motor	Bosch EB (L) 12V 0.8 (AL 50/20 W 12)
2 headlamps, high and low beams:	
with symmetric low beams ..	45/40 watts each (left hand drive countries only)
w/asymmetric low beams ...	45/40 watts each
2 clearance lights:	
in headlamps for all countries	
except USA:	
in directional blinkers for USA	4 watts each

2 tail lights (in blink/stop light units) ..	5 watts each
2 front directional blinkers	18 watts each
2 blink/stop light units	18 watts each
2 license plate light	4 watts each
1 backup light	25 watts

Interior lights:

2 in Coupe models	10 watts each
Tachometer illumination	2 watts
High beam indicator	2 watts
Blinker control lamp	2 watts
Combination instrument cluster illumination	2 watts
Alternator control lamp	2 watts
Oil pressure indicator lamp	2 watts
Speedometer illumination	2 watts

Transmission and Rear Axle

Type	integral transmission and differential
Transmission	4 forward speeds with Porsche synchronization, 5 speed transmission optional
Gear ratios	See Transmission Diagram, Group R
Reverse gear ratio	i = 3,1473
Gearshift mechanism	mechanical rod, floor mounted shift lever
Rear axle drive	spiral bevel gears, bevel gear differential, limited slip differential optional
Reduction ratio	i = 4,428

Chassis

Frame	welded sheetmetal box section frame unitized with body
Front wheel suspension	independently suspended on struts and transverse arms
Rear wheel suspension	independently suspended on triangulated links, with half-axle drive
Front wheel springing	1 round longitudinal torsion bar per wheel
Rear wheel springing	1 round transverse torsion bar per wheel
Rear radius arm attitude	Coupe = nominal inclination 39°
Front shockabsorbers	acting as suspension struts
Rear shockabsorbers	telescopic, double-action
Stabilizer	front, transverse mounted
Steering type	ZF rack and pinion
Steering ratio	1:16,5 overall
Steering wheel turns lock-to-lock ..	approx. 2,8
Smallest turning circle	approx. 10,5 m (34,4 ft)
Toe-in, front	± 0°
rear	0° ± 10'

Camber, front	0° ± 20'
Steering axis inclination	rear, -50' ± 20'
Caster	10° 55'
Angle variation	60° 45' ± 45'
Wheels	0° ± 30' (increasing toe-in)
Wheels	Steel
Drop center	5 1/2 x 15
Tires	165 HR 15
Nominal tire pressures:	
front	1.8 atm (26.5 psi)
rear	2.0 atm (29.4 psi)
Type service brake	disc
Service brake actuation	hydraulic
Total effective brake area	185 cm ² (28.7 sq. in.)
Brake disc diameter, front	282.5 mm (11.12")
rear	286.0 mm (11.26")
Parking brake	mechanical, acting on rear wheels
Body	
Type	all-steel body unitized with frame, declining front contour,
Doors	2 doors hinged on front posts
door width	1050 mm (41.3") overall
door swing angle	approx. 70°
Windows	one-piece, constant radius
windshield	cranked, with vent panel
rear side windows	hinged, with position lock
rear window	one-piece, curved
type of glass	safety glass
windshield wipers	electric, 2 parallel wiper arms
Compartment lids:	
front	hinged at rear, with hydraulic prop, opened from passenger compartment
rear	hinged at front, with hydraulic prop, opened from passenger compartment
seating capacity	2/2
front seats	2 fully reclining bucket-type seats
rear seats	2 occasional seats, folding forward to form luggage platform
instruments panel	illuminate speedometer with odometer and trip mileage counter, clearance light control lamp;
	illuminate electric tachometer with high beam indicator lamp,
	and directional blinker indicator lamp;
	illuminate oil temperature gauge with built in oil pressure and generator control lamps;
	illuminate fuel gauge with low-fuel indicator lamp;
	illuminate clock;
	windshield wiper switch (3-position) on steering post, ignition switch, light switch.

Instrument panel (cont'd)	cigarette lighter, ashtray, locking glove compartment, hand grip, blinker-dimmer-flasher switch on steering column, steering wheel with signal horn key (horn button for USA)
Interior trim:	
floor	lined with rubber mats
center tunnel	carpet lined
forward side panels	carpet lined
doors and side panels	upholstered
headlining	plastic lined
heating	remotely controlled hot air heating, 2 defroster nozzles at windshield, 2 hot air outlets in side members below doors
Ventilation	fresh air outlets thru defroster nozzles and outlets in side members below doors
Miscellaneous:	
bumpers	front and rear, with 2 overrides each
spare wheel	concealed under locked front lid
fuel tank	beneath luggage compartment
tools and accessories	in luggage compartment

Weights and Measures

Wheelbase	2211 mm	(87, 05")
Track, front	1367 mm	(53, 82")
rear	1335 mm	(52, 56")
Length	4163 mm	(163, 90")
Width	1610 mm	(63, 39")
Height, empty	1320 mm	(51, 97")
Body overhang, front	865 mm	(34, 06")
rear	1055 mm	(41, 54")
Ground clearance, loaded	150 mm	(5, 91")
Chassis clearance	140 mm	(5, 51")
Empty weight (DIN)	up to 31 Nov 67: 1080 kp (2376 lbs) from 1 Dec 67: 1020 kp (2244 lbs)	
Total permissible weight	1400 kp (3086 lbs)	
Maximum axle load, front	600 kp (1323 lbs)	
rear	840 kp (1852 lbs)	
Engine weight, complete but without oil	approx. 184 kp (406 lbs)	
Transaxle weight, complete with oil ...	approx. 50 kp (110 lbs)	

Capacities

Fuel tank	approx. 62 liters incl. 6 liters reserve (16,4 US gals incl 1, 6 gals reserve)
Engine and oil tank	approx. 9 liters premium HD oil (9, 5 US qts) summer SAE 30, winter SAE 20
Transaxle	approx. 2, 5 liters Hypoid SAE 90 (2, 6 US qts)
Brake fluid reservoir	approx. 0, 2 liters (7 fl. oz.)
Windshield washer reservoir	approx. 2, 0 liters (2, 1 US qts)

Performance

Horsepower rating	110 DIN HP (125 SAE HP) at 5800 rpm
Maximum torque	16 mkgp (131 ft-lb) at 4200 rpm
Mean piston speed at maximum power .	12.8 m/sec
Mean working pressure at maximum power	8.6 kp/cm ² (122 psi)
Minimum fuel consumption	210 g/HP at 3300 rpm
Maximum speed	200 kmh (125 mph)
Specific power output	55 DIN HP/liter (1.02 SAE HP/cu. in.)
Power/weight ratio (road ready)	10.4 kp/DIN HP (20.2 lbs/SAE HP)
Road speed in gears (theoretical)	see transmission diagram, Group R
Nominal fuel consumption	9 ltr/100 km (26 US mpg)
Required fuel octane rating	96 ROZ (research octane rating)

Fuel Consumption

TECHNICAL DATA

Vehicle type: 911 T

Engine type: 911 T

Engine

Type	Air cooled four cycle gasoline engine in unit with clutch, transmission and differential to form a single assembly at rear of vehicle
Number of cylinders	6
Cylinder arrangement	Horizontally opposed, three cylinders in each bank
Bore	80 mm (3,15")
Stroke	66 mm (2,60")
Total piston displacement	1991 cc
Compression ratio	8,6 : 1
Compression test pressure	9 - 11 kp/cm ² (128 - 157 psi) after 12 compression strokes
Total dry weight	Approx. 184 kg (406 lbs)
Crankcase	Two-part, light alloy
Cylinders	Individual
Cylinder material	Grey cast iron
Cylinder heads	Individual for each cylinder, light alloy
Valve seat inserts	Shrunk in
Valve guides	Shrunk in, special bronze
Spark plug seats	Helicoil inserts
Crankshaft	Forged
Crankshaft main bearings	8 plain bearings
Main bearings 1 thru 7	Split half shells, tri-metal
Main bearing 8	One piece, hard lead
Main bearing 1	Thrust bearing
Connecting rods	Forged steel
Big end bearings	Tri-metal
Piston pin bushings	Kuprodur, machined
Pistons	Die cast, Autotherm.
Piston rings	2 compression rings, 1 oil scraper
Valve operation	OHC, 1 camshaft per cylinder bank
Camshafts	Cast steel, 3 plain bearings directly in camshaft housing
Camshaft drive	Chains
Valve arrangement	Overhead
Valve springs	2 coil springs per valve
Valve test clearance (adjust with engine cold)	
Inlet	0,10 mm (0,004")
Exhaust	0,10 mm (0,004") - measure between valve and rocker arm
Valve timing with 1 mm (0,04") valve clearance	
Inlet opens before TDC	15°
Inlet closes after BDC	29°
Exhaust opens before BDC	41°
Exhaust closes before TDC	5°
Cooling	Air cooled by axial blower on generator shaft
Blower drive	From crankshaft by V-belt

Blower air flow	1320 liters (47 cu. ft.)/sec at 5800 rpm
Lubrication	Dry sump, forced feed
Oil cooling	Oil cooler on crankcase in blower air stream
Oil pressure gauge	Electrically controlled
Ignition	Battery and coil
Coil	TK 12 A 10 mV
Distributor	Marelli S 112 A X
Contact breaker gap	0.4 ± 0.03 mm (0.016 ± 0.0012"), dwell angle 40° ± 3°
Ignition point	35° BTDC at 6000 rpm
Firing order	1 - 6 - 2 - 4 - 3 - 5
Spark plugs	Bosch W 230 T 30
Spark plug threads	Beru 240/14/8
Electrode gap	14 x 1.25 mm
	0.6 mm (0.024")
Clutch	
Type	Fichtel and Sachs - M 215 K single dry plate
Free travel at pedal	Approx. 20 mm (0.8")
Total friction area	203 cm ² (31.5 sq. in.)
Fuel system	
Carburetors	Weber Type 40 IDT 3 C or IDT 3 C 1
Air cleaner	Inake silencer with Micronic filter element
Fuel pump	1 Hardi electric
Fuel delivery pressure	0.28 - 0.30 atm (4.1 - 4.5 psi)
Fuel delivery rate	900 cc (30.4 fl. oz.)/min.
Fuel pre-filter	Mesh screen in fuel tank
Fuel filter	Micro-filter in fuel pump
Electrical system	
Operating voltage	12 V
Batteries	2 x 12 V, 36 A mp/hr
Alternator	Motorola 14 V 770 W
Regulator	Motorola
Crankshaft-generator shaft ratio	Approx. 1 : 1.4
Starter	Bosch EB (12 V 0.8 hp)
2 headlights, high an low beam (Halogen)	Each 2 x H 1 55 W
2 headlights, high an low beam (standard bulbs) with symmetrical low beams (for driving on left only)	Each 45/40 W
2 clearance lights	Each 45/40 W
for all countries except USA, in headlights	Each 4 Watt
for USA, in front turn indicators	

4 side position lights in front and rear turn indicators (USA only)....	Each 4 Watt
2 tail lights in turn/stop tail light cluster)	Each 5 Watt
Emergency warning flashers (front and rear turn indicators)	
2 front turn indicators	Each 18 Watt
2 rear turn/stop/lights	Each 18 Watt
2 license plate lights	Each 4 Watt
1 backup light	25 Watt
Interior lights - Coupé (2)	Each 10 Watt
Glove box light	10 Watt
Tachometer lighting	2 Watt
High beam control lamp	2 Watt
Turn indicator control lamp	2 Watt
Combined instrument cluster lighting	2 Watt
Battery charge control lamp	2 Watt
Oil pressure warning lamp	2 Watt
Speedometer lighting	2 Watt
Fuses	
Window lift, windshield wipers, emergency warning light	25/40 Amp
Cigar lighter, stop lights, electric sliding roof	16/25 Amp
High and low beam headlights	8/15 Amp
Turn indicators, position lights, license plate lights	5/ 9 Amp

Transmission and rear axle

Type	Integral manual shift gearbox and differential
Gearbox	4 forward speeds with Porsche servo synchromesh; 5-speed gearbox optional
Gear ratios	1st - 4th or 1st - 5th; see transmission diagram, Group R
Reverse gear ratio	3,1473 : 1
Gear shift	Manual rod linkage, ball pivot floor mounted center shift lever
Rear axle drive	Spiral bevel pinion and crownwheel, bevel gear differential; optional limited slip differential
Rear axle ratio	4,428 : 1

Chassis

Frame	Welded sheet metal box section frame in unit with body
Front suspension	Independent, spring struts and lower wishbones
Rear suspension	Independent, semi-trailing arms and half shafts
Front springs	1 round section longitudinal torsion bar per wheel
Rear springs	1 round section transverse torsion bar per wheel
Rear radius arm attitude (nominal) ..	36°30' - 37°

Front shock absorbers	Acting as suspension struts
Rear shock absorbers	Double acting, telescopic
Steering	ZF-track and pinion
Total ratio	17.78 : 1 (average)
Steering wheel turns lock to lock	Approx. 3.1
Smallest turning circle	Approx. 10.7 m (35.1 feet)
Toe-in, front	0°
Toe-in, rear	0° ± 10'
Camber, front	0° ± 20'
Camber, rear	-50' ± 20'
Steering axis inclination	10°55'
Caster	6°45' ± 45'
Toe-out on turns, 20° wheel lock	0° - 30' increasing toe-in
Wheels	Steel rim
Rims	5 1/2 J x 15, drop center
Tires	165 HR 15
Tire pressures (nominal), front	1.8 atm (26.5 psi)
Tire pressures (nominal), rear	2.0 atm (29.5 psi)
Service brake (foot brake)	Disc (rwin circuit)
Service brake actuation	Hydraulic
Total effective brake area	210 cm ² (32.55 sq. in.)
Disc brake diameter, front	282.5 mm (11.12")
Disc brake diameter, rear	290 mm (11.42")
Effective brake disc diameter, front	235 mm (9.25")
Effective brake disc diameter, rear	244 mm (9.61")
Parking brake	Mechanical, acting on both rear wheels
Body	
Type	All steel body in unit with frame, declining front contour, fast-back rear on Coupe
Doors	2 doors, front hinged
Width	1050 mm (41.3") average
Opening angle	Approx. 70°
Windows	One piece, constant radius
Windshield	Crank action wind down windows
Door side windows	Front hinged, with position lock
Rear window	One piece, curved, electrically heated
Type of glass	Safety glass
Windshield wipers	Electric, 2 parallel action arms
Compartment lids	
Front	Rear hinged, with hydraulic prop, opened from car's interior
Rear	Front hinged, with hydraulic prop, opened from car's interior
Seats	2 / 2
Seating capacity	2 adjustable fully reclining bucket seats
Front seats	2 occasional seats, folding forward to form luggage platform
Rear seats	

Dashboards	Speedometer with total and trip distance recorders, side-light telltale, illuminated Electric revolution counter with built-in telltales for high beam and turn indicators, illuminated Oil temperature gauge with built-in oil pressure and generator telltale, illuminated Fuel gauge with reserve warning light, illuminated Clock, illuminated 3-position switch for windshield wipers on steering column outer tube Ignition/starter switch, main light switch Cigar lighter, ashtray, lockable glove box, grab handle Turn indicator/low beam/headlight flasher switch on steering column Steering wheel with horn push
Interior equipment	
Floor	Fitted carpet
Center tunnel	Carpet trim
Front side panels	Carpet trim
Doors and side panels	Upholstered
Roof lining	Plastic material
Heating	Remote controlled warm air heater with hot and cold air mixing, 2 defroster nozzles for windshield and 2 warm air outlets inside members below the doors Flap controlled fresh air plenum chamber, with 3-speed blower and air distribution system, centralized control unit
Ventilation	
Various	
Bumpers	Front and rear, each with two overrider horns
Spare wheel	Theft-proof mounting under front lid
Fuel tank	In front compartment
Tools and accessories	In front compartment
Dimensions and weights	
Wheelbase	2268 mm (89, 3")
Track front	1362 mm (53, 6")
rear	1343 mm (52, 8")
Length	4163 mm (163, 8")
Width	1610 mm (63, 4")
Height (unladen)	1320 mm (52, 0")
Overhang, front	865 mm (34, 1")
rear	1055 mm (41, 6")
Ground clearance (laden)	150 mm (5, 9")
Ground clearance between wheels	140 mm (5, 5")
Dry weight (DIN)	1020 kg (2249 lbs)
Permitted total weight	1400 kg (3087 lbs)
Permitted axle load	
front	600 kg (1323 lbs)
rear	840 kg (1773 lbs)
Weight of engine, ready to install, without oil	184 kg (406 lbs)
Weight of transmission, ready to install, with oil	50 kg (110 lbs)

Filling capacities	
Fuel tank	Approx. 62 liters (16.4 US gal.), including 6 liters (1.6 US gal.) reserve
Engine and oil tank	Approx. 9 liters (19 US pints) branded HD oil in summer SAE 30, in winter SAE 20 for temperatures from -15°C (+5°F) to 0°C (32°F), SAE 10 for temperatures below -15°C (+5°F)
Transmission and differential	Approx. 2.5 liters (5.3 US pints) SAE 90 hypoid
Brake fluid reservoir	Approx. 0.2 liters (0.42 US pints)
Windshield washer	Approx. 2 liters (4.2 US pints)
Performance	
Output	110 BHP (DIN)
at engine speed	5800 rpm
Maximum torque	16 mkgp (116 lb/ft)
at engine speed	4200 rpm
Mean piston speed	12.8 m/sec (2520 ft/min)
at maximum output	
Mean effective pressure	8.6 kp/cm ² (122.3 psi)
at maximum engine output	230 g/BHP/hr
Min. fuel consumption	3300 rpm
at engine speed	200 kph (124 mph)
Maximum road speed	55 BHP
Output per liter	9.9 kg. (21.8 lbs)/BHP (DIN)
Power/weight ratio (ready for road)	Speeds in indirect ratios (theoretical)
	Fuel consumption
	Fuel consumption (standard test method)
	9 liters per 100 km (26 US mpg)
	96 (RM)
	Min. octane rating

See transmission diagrams, group R

TECHNICAL DATA

Vehicle type: 911 E

Engine type: 911 E

Engine

Type	Air cooled four-stroke gasoline engine combined to form a single unit with clutch, transmission and rear axle. Mounted at rear of vehicle	
Number of cylinders	6	
Cylinder layout	Horizontally opposed 3 x 3	
Bore	80 mm (3.150")	
Stroke	66 mm (2.598")	
Capacity	1991 cc (121.5 cu. in.)	
Compression ratio	9,1 : 1	
Compression test	9 - 11 kp/cm ² (128 - 157 psi) - after 12 compression strokes	
Total dry weight	Approx. 184 kg (406 lbs)	
Crankcase	Light alloy, two-part	
Cylinders	Separate cylinder blocks	
Cylinder material	Biral (cast-iron with light alloy fins)	
Cylinder heads	Separate, light alloy	
Valve seats	Shrink fit	
Valve guides	Shrink fit, special bronze	
Spark plug seats	Heli-coil inserts	
Crankshaft	Forged	
Main bearings	8 plain bearings	
Main bearings 1 - 7	3-layer split shells	
Main bearing 8	1 piece bushing, hard lead	
Main bearing 1	Guide bearing	
Connecting rods	Forged steel, soft nitrided	
Big end bearings	3-layer	
Piston pin bushings	Kuprodur, turned	
Pistons	Light alloy, forged, box section	
Piston rings	2 compression rings, 1 oil scraper	
Valve operation	One overhead camshaft for each cylinder bank	
Camshaft	Cast, with 3 plain bearings mounted directly in cambox	
Camshaft drive	Chains	
Valve layout	Overhead	
Valve springs	2 coil springs per valve	
Valve clearances (adjust with engine cold)		
Inlet	0, 10 mm (0,0039")	Measured between valve and rocker
Exhaust	0, 10 mm (0,0039")	
Valve test timing (measured with 1 mm/0,04" valve clearance)		
Inlet opens before TDC	29°	
Inlet closes after BDC	39°	
Exhaust opens before BDC	39°	
Exhaust closes after TDC	19°	
Cooling	Air cooled with axial blower on generator	
Blower drive	By V-belt from crankshaft	

1480 liters (52.5 cu. ft)/sec at 6500 rpm	Air flow rate.....
Dry sump with pressure oil circulation	Lubrication.....
Oil cooler on crankcase within flow from blower	Oil cooling.....
Electric	Oil pressure gauge.....
High tension battery/condenser ignition	Ignition.....
Bosch	Ignition transformer (coil).....
Bosch	Distributor.....
0.3 mm (0.012")	Contact breaker points (min.).....
30° before TDC at 6000 rpm	Ignition point.....
1 - 6 - 2 - 4 - 3 - 5	Firing order.....
W 265 P 21, W 265 T 2SP	Spark plugs.....
14 x 1.25 mm	Spark plug thread.....
0.35 mm (0.014")	Spark plug gap.....
Fichtel and Sachs - M 215 K single dry plate	Clutch pedal free travel.....
Approx. 20 mm (0.8")	Type.....
203 cm ² (31 sq. in.)	Total lining area.....
Bosch 6 element double row injection pump	Fuel injection.....
Intake air muffler with Micronic element	Air cleaner.....
One electric fuel pump	Fuel pump.....
0.8 ± 0.2 atm (11.38 ± 2.84 psi)	Delivery pressure of electric pump.....
approx. 110 liters (29.1 US gal.)/hr.	Flow rate of electric pump.....
Mesh filter in fuel tank	Fuel purification.....
Micro filter in front of injection pump with built-in resistor	Fuel filter.....
12 Volt	Service voltage.....
2 x 12 Volt, 36 amp/hr.	Batteries.....
Bosch K 1 - 14V 770 W	Generator.....
Bosch VDN 1	Regulator.....
A approx. 1 : 1.4	Crankshaft - Generator shaft.....
Bosch EB (12 V 0.8 hp)	Starter.....
Each 2 x H 1 55 W	2 Headlights, high and low beam (Quartz-Iodine).....
Each 45/40 Watt	2 Headlights, high and low beam (spherical bulbs with vertical dimming) for countries driving on left only.....
Each 45/40 Watt	for asymmetric low beam.....
Each 4 Watt	2 side lights.....
	for all countries except USA,
	inside headlight units
	for USA, in front turn indicators,

Electrical system

Fuel system

Clutch

4 side boundary lights in front and rear turn indicators (USA only)	Each 4 Watt
2 rear lights in turn indicator - stop - rear light units	Each 5 Watt
Emergency warning flasher system (front and rear turn indicators)	
2 front turn indicators	Each 18 Watt
2 turn indicator - stop lights	Each 18 Watt
2 license plate lights	Each 4 Watt
1 reversing light	25 Watt
Interior light (2 fitted to Coupé)	Each 10 Watt
Glove box light	10 Watt
Revolution counter - instrument lighting	2 Watt
High beam telltale	2 Watt
Turn indicator telltale	2 Watt
Combined instrument lighting	2 Watt
Generator telltale	2 Watt
Oil pressure telltale	2 Watt
Speedometer lighting	2 Watt
Fuses	
Window lifts, windshield wipers, emergency warning light	25/40 Amp.
Cigar lighter, stop light, sliding roof	16/25 Amp.
High beam, low beam	8/15 Amp.
Turn indicators, side lights, license plate lights	5/ 9 Amp.

Transmission and rear axle

Type	5-speed gearbox and differential in combined housing
Manual gearbox	5 forward gears with Porsche servo synchromesh
For 1st to 5th gear ratios, see gearbox diagram, group R	
Reverse gear ratio	3.1473 : 1
Gear shift	Rod linkage with ball joint gear shift lever in center of floor
Final drive	Spiral bevel pinion, bevel pinion differential option; limited-slip differential
Rear axle ratio	4.428 : 1

Chassis

Frame	Welded box section steel feet, welded to superstructure
Suspension, front	Independent, with wishbones and spring struts
rear	Independent, semi-trailing arms, drive to rear wheels by half shafts
Springing, front	1 self-levelling hydropneumatic spring strut per wheel
rear	1 round section torsion bar, horizontally mounted, per wheel
Rear radius arm settings (approx. alignment value)	36°30' - 37°

Shock absorbers, front	
Shock absorbers, rear	
Steering	
Overall ratio	
Number of turns of steering wheel	
from lock to lock	
Mfn. turning circle	
Toe-in, front	
Toe-in, rear	
Camber, front	
Camber, rear	
Knoppin inclination	
Castor	
Toe-out at 20° wheel lock	
Wheels	
Rims	
Tire pressures (suggested), front	
Tire pressures (suggested), rear	
Service brake (foot brake)	
Service brake operating system	
Effective total rubbing area	
Brake disc diameter, front	
Brake disc diameter, rear	
Effective brake disc diameter	
from	
rear	
Parking brake	
Operates mechanically on both rear wheels	
228 mm (8.97 in.)	
244 mm (9.61 in.)	
Disc brakes	
Hydraulic	
257 cm ² (39.2 sq. in.)	
282.8 mm (11.1 in.), internally ventilated	
290 mm (11.4 in.), internally ventilated	
2.4 atm (34 psi)	
2.0 atm (28 psi); for speeds above 200 kph (124 mph):	
2.2 atm (31 psi)	
1.8 atm (26 psi); for speeds above 200 kph (124 mph):	
Light alloy, forged	
0° to 30° towards toe-in	
60°45' ± 45'	
10°55' ± 20'	
0° ± 20'	
0° ± 10'	
0°	
Aprox. 10.7 meters (35 ft. 2 in.)	
Aprox. 3.1	
17.78 : 1 (at straight ahead position)	
ZF - rack and pinion	
Double acting telescopic shock absorbers	
In spring strut	
Type	
Doors	
Width	
Opening angle	
Windows	
Windshield	
Door windows	
Rear side windows	
Rear window	
Type of glass	
Windshield wipers	
Opening panels	
front	
rear	
Seats	
Number of seats	
front	
rear	
2 separate adjustable seats with reclining mechanisms	
2 emergency seats with seat backs folding forwards to provide	
a baggage shelf	
2 / 2	
Top hinged, with hydraulic prop, released from inside the car	
Rear hinged, with hydraulic prop, released from inside the car	
One piece, curved in both planes	
Fully retracting winding windows	
Front hinged with locking catch	
Full width, curved, electrically heated	
Safety glass	
Electric, 2 parallel wiper arms	
fast back on Coupe model	
2 doors, front hinged	
1050 mm (41.3 in.) mean width	
Aprox. 70°	
All steel body shell welded to frame, dropped nose section,	

Superstructure